

Searches for User *gverbitsky* (Count = 41132)

Queries 41083 through 41132.

Find	<input type="text"/>
First	Next
Previous	Oldest
Edit	Help
Return	

S #	Updt	Database	Query
S41132	U	PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD	((three layer\$2 insulat\$3) adj5 (thermist (adhesive or glue)
S41131	U	PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD	(three layer\$2 insulat\$3) adj5 (thermist
S41130	U	PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD	multilayered resist\$4 insulation
S41129	U	PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD	multilayered thermistor insulation
S41128	U	PGPB,USPT,USOC,EPAB,JPAB	((374/185,57,141,152,45,47,4,208;324/5. [CCLS] and (temperature or thermal or t resist\$4 or resist\$4) and (resistive elemen thermal resist\$4 or thermal probe)) and temperature or transformer adj5 tempera temperature or rotor adj5 temperature)
S41127	U	PGPB,USPT,USOC,EPAB,JPAB	((374/185,57,141,152,45,47,4,208;324/5. [CCLS] and (electric\$2 machine or trans rotor or electric\$2 element or electric\$2 (resistive element or thermistor or therm thermal probe)
S41126	U	PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD	(\$5layer\$2 insulat\$3) same (winding)
S41125	U	PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD	\$5layer\$2 insulat\$3
S41124	U	PGPB,USPT,USOC,EPAB,JPAB	((laminat\$3 insulat\$4 or multilayer\$2 ins (resistive element or thermistor or therm thermal probe)) and (winding)
S41123	U	PGPB,USPT,USOC,EPAB,JPAB	((laminat\$3 insulat\$4 or multilayer\$2 ins (resistive element or thermistor or therm thermal probe)

S41122 U PGPB,USPT,USOC,EPAB,JPAB

S41121 U PGPB,USPT,USOC,EPAB,JPAB

S41120 U PGPB,USPT,USOC,EPAB,JPAB

S41119 U PGPB,USPT,USOC,EPAB,JPAB

S41118 U PGPB,USPT,USOC,EPAB,JPAB

S41117 U PGPB,USPT,USOC,EPAB,JPAB

S41116 U PGPB,USPT,USOC,EPAB,JPAB

S41115 U PGPB,USPT,USOC,EPAB,JPAB

S41114 U PGPB,USPT,USOC,EPAB,JPAB

(laminat\$3 insulat\$4 or multilayer\$2 insi

((374/185,57,141,152,45,47,4,208;324/5.
[CCLS] and (resist\$4 insulat\$4 or thermi
(laminat\$3 insulat\$4)

((374/185,57,141,152,45,47,4,208;324/5.
[CCLS] and (resist\$4 insulat\$4 or thermi
(multilayered insulat\$4)

((374/185,57,141,152,45,47,4,208;324/5.
[CCLS]) and (resist\$4 insulat\$4 or therr

((374/185,57,141,152,45,47,4,208;324/5.
[CCLS] and (temperature or thermal or t
resist\$4 or resist\$4)) and (resist\$4 insula

((374/185,57,141,152,45,47,4,208;324/5.
[CCLS] and (temperature or thermal or t
resist\$4 or resist\$4)) and (winding insul.

((374/185,57,141,152,45,47,4,208;324/5.
[CCLS]) and (temperature or thermal or
thermal resist\$4 or resist\$4)

((374/185,57,141,152,45,47,4,208;324/5.
[CCLS]) and (electric\$2 machine or trar
rotor or electric\$2 element or electric\$2
(374/185,57,141,152,45,47,4,208;324/52
[CCLS]